

#### Applications

- WiFi bandpass filter that enables the coexistence of 4G (WiMAX/LTE/TD-LTE) & WiFi signals
- Handsets
- Portable Hotspots
- Mobile Routers
- Smart Meters
- High-power WLAN Access Points
- Applicable reject bands: 2.6 GHz WiMAX/LTE, LTE Bands 7 & 41

#### Product Features


- Low Loss in WLAN band with extended upper corner for inclusion of Bluetooth
- High Rejection in B7/B41 bands
- Industry leading small size: 1.4 x 1.2 x 0.46 mm
- Performance over -30 to +85 °C
- Single Ended operation
- Hermetically sealed
- RoHS compliant, Pb-free module package

#### General Description

The 885032 is a high-performance, high power Bulk Acoustic Wave (BAW) band-pass filter with extremely steep skirts, simultaneously exhibiting low loss in the WiFi band and high near-in rejection in the 2.6GHz bands.


885032 is specifically designed to enable coexistence of WiFi and LTE signals within the same device or in close proximity to one another.

The 885032 uses common module packaging techniques to achieve the industry standard 1.4 x 1.2 x 0.46 mm footprint. The filter exhibits excellent power handling capabilities.



CSP-5CT package: 1.4x1.2x0.46mm

#### Functional Block Diagram



#### Pin Configuration

Pin No.	Label
1	Input
4	Output
2,3,5	Ground

#### Ordering Information

Part No.	Description
885032	Packaged part
885032-EVB	Evaluation board

Standard T/R size = 15,000 units/reel

## Absolute Maximum Ratings

Parameter	Rating
Storage Temperature <sup>(1)</sup>	-40 to +85°C
Operable Temperature <sup>(2)</sup>	-30 to +85°C
Absolute Maximum input power <sup>(3)</sup>	+31 dBm

1. Operation of this device outside the parameter ranges given may cause permanent damage.
2. Specifications are not guaranteed over all operable conditions.
3. (X) Maximum CW signal applied for up to 100 msec with no damage.

## Electrical Specifications <sup>(1)</sup>



Conditions unless otherwise noted: Device Temperature = -30°C to +85°C.

Parameter <sup>(2)</sup>	Conditions	Min	Typ (+25°C)	Max	Units
Insertion Loss <sup>(3)</sup>	2402.5 – 2421.5 MHz (WiFi Ch.1)	-	1.6	1.9	dB
	2407.5 – 2426.5 MHz (WiFi Ch.2)		1.3	1.7	
	2412.5 – 2471.5 MHz (WiFi Ch.3-11)		1.5	2.0	
	2457.5 – 2476.5 MHz (WiFi Ch.12)		1.7	2.2	
	2462.5 – 2481.5 MHz (WiFi Ch.13)		1.9	2.8	
Passband Ripple	2402.5 – 2421.5 MHz (WiFi Ch.1)	-	1.0	-	dB
	2407.5 – 2426.5 MHz (WiFi Ch.2)		1.0		
	2412.5 – 2471.5 MHz (WiFi Ch.3-11)		0.8		
	2457.5 – 2476.5 MHz (WiFi Ch.12)		0.8		
	2462.5 – 2481.5 MHz (WiFi Ch.13)		1.7		
VSWR, In & Out	2402.5 – 2476.5 MHz (WiFi Ch.1-12)	-	1.9	2.1	-
	2462.5 – 2481.5 MHz (WiFi Ch.13)		1.8	3.2	
Impulse Response Length <sup>(4)</sup>	2401 – 2483 MHz	-	160	200	ns
Rejection/Attenuation	100 – 2300 MHz	37	39	-	dB
	2300 – 2370 MHz <sup>(5)</sup>	50	53	-	dB
	2496 – 2501 MHz (+25 to +85°C) <sup>(5)</sup>	32	55	-	dB
	2496 – 2501 MHz (-30 to +25°C) <sup>(5)</sup>	18	55		
	2500 – 2505 MHz (+25 to +85°C) <sup>(5)</sup>	50	57	-	dB
	2500 – 2505 MHz (-30 to +25°C) <sup>(5)</sup>	38	57		
	2505 – 2570 MHz (+25 to +85°C) <sup>(5)</sup>	49	54	-	dB
	2505 – 2570 MHz (-30 to +25°C) <sup>(5)</sup>	49	54		
	2570 – 2620 MHz <sup>(5)</sup>	45	49	-	dB
	2620 – 2690 MHz <sup>(5)</sup>	44	47	-	dB
4800 – 5000 MHz	37	48	-	dB	
7200 – 7500 MHz	31	38	-	dB	
2 <sup>nd</sup> Harmonics	CW Tone = 2442MHz @ 22.5dBm	-	60	-	dBc
3 <sup>rd</sup> Harmonics	CW Tone = 2442MHz @ 22.5dBm	-	138	-	dBc
RF Input Power <sup>(7)</sup>	2400-2481.5 MHz	27			dBm

**Notes:**

1. In production, devices will be tested at room temperature to a guard-banded specification to ensure electrical compliance over temperature
2. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
3. Data is the integrated value of the linear s-parameter over the indicated band at the specified temperature.
4. Duration in ns between the maxima and the point 40 dB below the maxima.
5. Data is the integrated value of the linear s-parameter over 5MHz range at the specified temperature.
6. An external impedance matching network with  $\pm 2\%$  tolerance will be necessary to achieve the stated specifications. This is the optimum impedance in order to achieve the performance shown
7. Input power applied at 50% duty cycle for a minimum of 5,000 hrs at 55°C in the frequency band specified.

**Evaluation Board**




**Notes:**

1. Matching component values shown are for the specified TriQuint evaluation board. Value adjustment may be required in end user product circuits depending on component manufacturer and PCB material.

**Bill of Material**

Reference Des.	Value	Description	Manuf.	Part Number
L1	9.1 nH	Chip Inductor, 0201, +/- 2%	Murata	
L2	15 nH	Chip Inductor, 0201, +/- 2%	Murata	
PCB	N/A	3-layer	Multiple	961000

**PCB Mounting Pattern**




**Notes:**


1. All dimensions are in millimeters. Angles are in degrees.
2. This drawing specifies the mounting pattern used on the TriQuint evaluation board for this product. Some modification may be necessary to suit end user assembly materials and processes.

Performance Plots

Test conditions unless otherwise noted: Temp= +25°C



Package Information, Marking and Dimensions



Package Style: CSP-5CT  
Dimensions: 1.4 x 1.2 x 0.46 mm


Body:  $Al_2O_3$  ceramic  
Lid: Kovar or Alloy 42, Au over Ni plated  
Terminations: Au plating 0.5 - 1.0 $\mu$ m, over a 2-6 $\mu$ m Ni plating

The date code consists of: WW = 2 digit week,  
Y = last digit of year, M = manufacturing site code

An asterisk (\*) in front of the marking code indicates prototype.

All dimensions shown are nominal in millimeters  
All tolerances are  $\pm 0.05$ mm except overall length and width  $\pm 0.10$ mm

Tape and Reel information



Standard T/R size=15,000 units/reel. All dimensions are in millimeters.

## Product Compliance Information

### ESD Sensitivity Ratings



Caution! ESD-Sensitive Device

ESD Rating: Class 1B  
Volt. Range: 500 to < 1000 Volts  
Test: Human Body Model (HBM)  
Standard: JEDEC JS-001

ESD Rating: TBD  
Volt. Range: TBD  
Test: Charge Device Model (CDM)  
Standard: JEDEC JS-002

### MSL Rating

Not applicable. Hermetic package.

### Solderability

Compatible with the latest version of J-STD-020, lead free solder, 260°C

Refer to [Soldering Profile](#) for recommended guidelines.

### RoHs Compliance

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C<sub>15</sub>H<sub>12</sub>Br<sub>4</sub>O<sub>2</sub>) Free
- PFOS Free
- SVHC Free

## Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

**Web:** [www.triquint.com](http://www.triquint.com)  
**Email:** [customer.support@qorvo.com](mailto:customer.support@qorvo.com)

**Tel:** 877-800-8584

For information about the merger of RFMD and TriQuint as Qorvo:

**Web:** [www.qorvo.com](http://www.qorvo.com)

For technical questions and application information:

**Email:** [flapplication.engineering@tqs.com](mailto:flapplication.engineering@tqs.com)

## Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.