

CSD18534KCS 60 V N-Channel NexFET™ Power MOSFET

1 Features


- Ultra-Low Q_g and Q_{gd}
- Low Thermal Resistance
- Avalanche Rated
- Logic Level
- Pb-Free Terminal Plating
- RoHS Compliant
- Halogen Free
- TO-220 Plastic Package

2 Applications

- DC-DC Conversion
- Secondary Side Synchronous Rectifier
- Motor Control

3 Description

This 7.6 mΩ, 60 V TO-220 NexFET™ power MOSFET has been designed to minimize losses in power conversion applications.



Product Summary

| $T_A = 25^\circ\text{C}$ | | TYPICAL VALUE | | UNIT |
|--------------------------|-------------------------------|-------------------------|------|------|
| V_{DS} | Drain-to-Source Voltage | 60 | | V |
| Q_g | Gate Charge Total (10 V) | 19 | | nC |
| Q_{gd} | Gate Charge Gate to Drain | 3.1 | | nC |
| $R_{DS(on)}$ | Drain-to-Source On Resistance | $V_{GS} = 4.5\text{ V}$ | 10.2 | mΩ |
| | | $V_{GS} = 10\text{ V}$ | 7.6 | mΩ |
| $V_{GS(th)}$ | Threshold Voltage | 1.9 | | V |

Ordering Information

| Device | Package | Media | Qty | Ship |
|-------------|------------------------|-------|-----|------|
| CSD18534KCS | TO-220 Plastic Package | Tube | 50 | Tube |

Absolute Maximum Ratings

| $T_A = 25^\circ\text{C}$ | | VALUE | UNIT |
|--------------------------|--|------------|------|
| V_{DS} | Drain to Source Voltage | 60 | V |
| V_{GS} | Gate to Source Voltage | ±20 | V |
| I_D | Continuous Drain Current (Package limited) | 100 | A |
| | Continuous Drain Current (Silicon limited), $T_C = 25^\circ\text{C}$ | 73 | |
| | Continuous Drain Current (Silicon limited), $T_C = 100^\circ\text{C}$ | 52 | |
| I_{DM} | Pulsed Drain Current ⁽¹⁾ | 111 | A |
| P_D | Power Dissipation | 107 | W |
| T_J, T_{stg} | Operating Junction and Storage Temperature Range | -55 to 175 | °C |
| E_{AS} | Avalanche Energy, single pulse $I_D = 38\text{ A}, L = 0.1\text{ mH}, R_G = 25\ \Omega$ | 72 | mJ |

(1) Pulse duration $\leq 300\ \mu\text{s}$, duty cycle $\leq 2\%$





Table of Contents

| | | | |
|--------------------------------------|----------|---|----------|
| 1 Features | 1 | 5.3 Typical MOSFET Characteristics | 4 |
| 2 Applications | 1 | 6 Device and Documentation Support | 7 |
| 3 Description | 1 | 6.1 Trademarks | 7 |
| 4 Revision History | 2 | 6.2 Electrostatic Discharge Caution | 7 |
| 5 Specifications | 3 | 6.3 Glossary | 7 |
| 5.1 Electrical Characteristics | 3 | 7 Mechanical, Packaging, and Orderable Information | 8 |
| 5.2 Thermal Information | 3 | 7.1 KCS Package Dimensions | 9 |

4 Revision History

| Changes from Original (September 2012) to Revision A | Page |
|---|----------|
| • Updated document title | 1 |
| • Updated description | 1 |
| • Adjusted currents to reflect higher temperature capability in Absolute Maximum Ratings | 1 |
| • Adjusted max power to reflect higher temperature capability in Absolute Maximum Ratings | 1 |
| • Increased maximum temperature to 175°C in Absolute Maximum Ratings | 1 |
| • Updated Figure 6 to extend to 175°C | 5 |
| • Updated Figure 8 to extend to 175°C | 5 |
| • Updated Figure 12 to extend to 175°C | 6 |

5 Specifications

5.1 Electrical Characteristics

 $T_A = 25^\circ\text{C}$ unless otherwise stated

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--------------------------------|----------------------------------|---|---|------|------|---------------|
| STATIC CHARACTERISTICS | | | | | | |
| V_{DSS} | Drain-to-Source Voltage | $V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$ | 60 | | | V |
| I_{DSS} | Drain-to-Source Leakage Current | $V_{GS} = 0\text{ V}, V_{DS} = 48\text{ V}$ | | | 1 | μA |
| I_{GSS} | Gate-to-Source Leakage Current | $V_{DS} = 0\text{ V}, V_{GS} = 20\text{ V}$ | | | 100 | nA |
| $V_{GS(th)}$ | Gate-to-Source Threshold Voltage | $V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$ | 1.5 | 1.9 | 2.3 | V |
| $R_{DS(on)}$ | Drain-to-Source On Resistance | $V_{GS} = 4.5\text{ V}, I_D = 40\text{ A}$ | | 10.2 | 13.3 | m Ω |
| | | $V_{GS} = 10\text{ V}, I_D = 40\text{ A}$ | | 7.6 | 9.5 | m Ω |
| g_{fs} | Transconductance | $V_{DS} = 30\text{ V}, I_D = 40\text{ A}$ | | 100 | | S |
| DYNAMIC CHARACTERISTICS | | | | | | |
| C_{iss} | Input Capacitance | $V_{GS} = 0\text{ V}, V_{DS} = 30\text{ V}, f = 1\text{ MHz}$ | | 1500 | 1880 | pF |
| C_{oss} | Output Capacitance | | | 164 | 205 | pF |
| C_{rss} | Reverse Transfer Capacitance | | | 5.0 | 6.5 | pF |
| R_G | Series Gate Resistance | | | 1.5 | 3.0 | Ω |
| Q_g | Gate Charge Total (4.5 V) | $V_{DS} = 30\text{ V}, I_D = 40\text{ A}$ | | 9.3 | 12 | nC |
| Q_g | Gate Charge Total (10 V) | | | 19 | 24 | nC |
| Q_{gd} | Gate Charge Gate to Drain | | | 3.1 | | nC |
| Q_{gs} | Gate Charge Gate to Source | | | 4.8 | | nC |
| $Q_{g(th)}$ | Gate Charge at V_{th} | | | 3.3 | | nC |
| Q_{oss} | Output Charge | | $V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}$ | | 18 | |
| $t_{d(on)}$ | Turn On Delay Time | $V_{DS} = 30\text{ V}, V_{GS} = 10\text{ V}, I_{DS} = 40\text{ A}, R_G = 0\ \Omega$ | | 4.2 | | ns |
| t_r | Rise Time | | | 4.8 | | ns |
| $t_{d(off)}$ | Turn Off Delay Time | | | 10.4 | | ns |
| t_f | Fall Time | | | 2.4 | | ns |
| DIODE CHARACTERISTICS | | | | | | |
| V_{SD} | Diode Forward Voltage | $I_{SD} = 40\text{ A}, V_{GS} = 0\text{ V}$ | | 0.8 | 1 | V |
| Q_{rr} | Reverse Recovery Charge | $V_{DS} = 30\text{ V}, I_F = 40\text{ A}, di/dt = 300\text{ A}/\mu\text{s}$ | | 68 | | nC |
| t_{rr} | Reverse Recovery Time | | | 49 | | ns |




5.2 Thermal Information

 $T_A = 25^\circ\text{C}$ unless otherwise stated

| PARAMETER | | MIN | TYP | MAX | UNIT |
|-----------------|--|-----|-----|-----|---------------------------|
| $R_{\theta JC}$ | Junction-to-Case Thermal Resistance | | | 1.3 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JA}$ | Junction-to-Ambient Thermal Resistance | | | 62 | $^\circ\text{C}/\text{W}$ |

5.3 Typical MOSFET Characteristics

$T_A = 25^\circ\text{C}$, unless otherwise stated



Typical MOSFET Characteristics (continued)

T_A = 25°C, unless otherwise stated




Figure 4. Gate Charge




Figure 5. Capacitance




Figure 6. Threshold Voltage vs Temperature




Figure 7. On-State Resistance vs Gate-to-Source Voltage




Figure 8. Normalized On-State Resistance vs Temperature




Figure 9. Typical Diode Forward Voltage

Typical MOSFET Characteristics (continued)

$T_A = 25^\circ\text{C}$, unless otherwise stated




Figure 10. Maximum Safe Operating Area




Figure 11. Single Pulse Unclamped Inductive Switching




Figure 12. Maximum Drain Current vs Temperature

6 Device and Documentation Support

6.1 Trademarks

NexFET is a trademark of Texas Instruments.

6.2 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

6.3 Glossary


[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms and definitions.

7 Mechanical, Packaging, and Orderable Information

The following pages include mechanical packaging and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

7.1 KCS Package Dimensions



- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 - C Lead dimensions are not controlled within this area. Chamfer may or may not appear
 - D. All lead dimensions apply before solder dip.
 - E. The center lead is in electrical contact with the mounting tab.
 - F. The chamfer is optional.
 - G. Thermal pad contour optional within these dimensions.
 - H. Falls within JEDEC TO-220 variation AB, except minimum lead thickness, minimum exposed pad length, and maximum body length.

Terminal Configuration

| Position | Designation |
|------------------|-------------|
| Terminal 1 | Gate |
| Terminal 2 / Tab | Drain |
| Terminal 3 | Source |

PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead/Ball Finish (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|------------------|---------------|--------------|-----------------|------|-------------|-----------------------|-------------------------|----------------------|--------------|-------------------------|---------|
| CSD18534KCS | ACTIVE | TO-220 | KCS | 3 | 50 | Pb-Free (RoHS Exempt) | CU SN | N / A for Pkg Type | -55 to 150 | CSD18534KCS | Samples |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSELETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

| | |
|------------------------------|--|
| Audio | www.ti.com/audio |
| Amplifiers | amplifier.ti.com |
| Data Converters | dataconverter.ti.com |
| DLP® Products | www.dlp.com |
| DSP | dsp.ti.com |
| Clocks and Timers | www.ti.com/clocks |
| Interface | interface.ti.com |
| Logic | logic.ti.com |
| Power Mgmt | power.ti.com |
| Microcontrollers | microcontroller.ti.com |
| RFID | www.ti-rfid.com |
| OMAP Applications Processors | www.ti.com/omap |
| Wireless Connectivity | www.ti.com/wirelessconnectivity |

Applications

| | |
|-------------------------------|--|
| Automotive and Transportation | www.ti.com/automotive |
| Communications and Telecom | www.ti.com/communications |
| Computers and Peripherals | www.ti.com/computers |
| Consumer Electronics | www.ti.com/consumer-apps |
| Energy and Lighting | www.ti.com/energy |
| Industrial | www.ti.com/industrial |
| Medical | www.ti.com/medical |
| Security | www.ti.com/security |
| Space, Avionics and Defense | www.ti.com/space-avionics-defense |
| Video and Imaging | www.ti.com/video |

TI E2E Community

e2e.ti.com